

INFORMATION ON USSR COALS USED FOR COKING

Ugli dlya Koksovaniya i Kontrol'ikh Kachestva Metallurgizdat, Moscow, 1954

A. M. Kotkin Ya. M. Obukhovskiy

Extension of Coking Raw Material Base

Γ

Mines of the Donbass and Kuzbass work a large number of seams the coal of which is delivered under one name, but the quality indexes, that is, the sulfur content, the coking properties, and the ash content of coal of specific seams, vary even within the bounds of the mine field.

In the frequent absence of adequate devices for separate yield of seams and for effective standardization, coking coal shipped from one mine varies greatly in its coking properties and in its sulfur and ash content.

In some Donbass mines, commercial coals consist of a mixture of coals which cake slightly and those which cake well. Up to 30 percent of lean, slightly caking coal often goes into the total mixture, whereas the participation of these seams in the general output varies according to specific periods of operations.

In other mines, commercial coal consists of a blending of gas coal and PZh coal, a mixture of K and PZh, or K and PS coals.

Charges in coke by-products plants contain sharply varying amounts of lean coal in place of PS, PS in place of K, gas and contractir; (usadochnyy) coal in place of PZh, etc. This leads to a variation in the quality of the coke in mechanical properties and in sulfur content, a narrowing of the assort-caking K and PZh coals, which are supplied in a somewhat increased amount to the charge to insure the quality of the coke against variations in the quality of coals of specific mines.

If coals are correctly classified in groups according to their individual technological properties and if careful standardization of the coal is carried out at all stages, from the face to the coking chamber, it will be possible to expand considerably the raw-material base for coking and at the same time to improve the quality and uniformity of the coke.

In the Kuzbass, the extension of the assortment of coals for coking is dependent, first of all, on efficient exploitation of existing productive capacities. As a result of experiments with coal conducted in recent years and also of perfecting the technology of preparing it, a considerable amount of Kuzbass coal with lowered coking properties has been included in coking charges (coal from the Moshchnyy and Gorelyy seams, among others).

In the Donbass, the extension of the raw-material base for coking is taking the direction, first of all, of lowering the sulfur content of metallurgical-coke, which is still very high (1.7-1.8 percent). About half of the reserves of basin explored to a depth of 600 meters consist of gas coal with a low sulfur content (up to 2.5 percent). Coals widely ved for coking of types K, KZh, and PS with such a sulfur content make up only one third of the reserves. A considerable amount of low-sulfur coal (sulfur content up to 1.5 percent) exists among the lean, noncaking coals, which constitute up to 18 percent of the reserves.

At present, the majority of southern coke by-products plants with coalcleaning facilities use up to 18-20 percent gas coal in their charges. Experiments in coking conducted in the Stalino, Krivoy Rog, and Novo-Makeyevka plants and experimental blast-furnace smeltings have indicated the possibility of raising the proportion of gas coal still more, to 25-30 percent.

The Stalino Coke By-Products Plant, after carrying out experimental coking for a long time, is operating successfully on a charge of 25 percent G coal, 30 percent PS coal, and 45 percent PZh. Blast furnaces of medium size operate satisfactorily on coke from this new charge.

The Krivoy Rog Coke By-Products Plant operated for 24 days on an experimental charge consisting of 30 percent G coal, 29 percent PZh, 18 percent K, and 23 percent PS. The large blast furnace which smelted open-hearth iron on this charge operated smoothly.

The Moscow Coke By-Products, put in operation in 1951, succeeded in converting to the following charge: 30 percent G coal, 30 percent PZh, 20 percent K, and 20 percent PS. The coke obtained is used in blast furnaces of Tula, Lipetsk, and in other metallurgical plants of the Central Region. The long practice of the Moscow Plant and the positive experiments in the Krivoy Rog Plant permit considering a charge with 30 percent gas coal as promising good results.

The Novo-Makeyevka Coke By-Products Plant conducted experimental coking with the following charge: 40 percent G coal, 23 percent PZh, 15 percent K, 22 percent PS. According to the conclusion of the Ukrainian Metals Institute, the conversion to the experimental coke did not have any marked effect on the operation of the blast furnaces.

The introduction into the charge of gas coal has improved the output of the chemical products of coking, the benzene hydrocarbons and tars, and it has facilitated the delivery of coke from the oven chambers. However, an increase in the proportion of gas coals leads to a decreased total output of coke and also of metallurgical coke, facts which must be taken into account.

Very important too is the addition to the coking charge of lean coals, which are bituminous coals with a very low volatile matter content, less than 17 percent.

Before 1950, Donbass lean coal was not used for coking. Recently, experiments have indicated that low-sulfur lean coal may be used to obtain foundry coke and, in some cases, when it is finely crushed, also for blast furnace coke.

The Khar'kov Plant conducted experimental coking with charges containing lean coal from Mine No 5 bis of the Voroshilovugol' Trust, which had a 5-percent ash and a 1.3-percent sulfur content and which had been completely crushed to class 0-3 millimeters. Coke with the best indexes for mechanical toughness was obtained from charges mixed in the rollowing proportions (in percent):

In the Smolyaninovskiy and Khanzhenkovskiy coke by-products plants and also in the Mushketovskiy coke ovens, 10 percent of lean coal subjected to ordinary crushing was introduced into the charge after suitable experimentation. The new charge contained 10 percent T coal, 35 percent K, and 55 percent KZh. The quality of the foundry coke was somewhat lowered, but it still satisfied requirements of the standard.



STAT

Special crushing installations were set up at the Novo-Makeyevka Plant to crush the coal approximately 100 percent to the 0-2-millimeter class. As a result, the plant obtains coke of satisfactory quality from a charge containing 5 percent T coal, 12 percent PS, 25 percent K, 16 percent G, and 42 percent PZh. The blast furnaces of the Makeyevka Metallurgical Plant imeni Kirov have been operating on this coke for a long time.

Considerable interest is also displayed in the use in the charge of long-flame D coal with a maximum volatile-matter content of over 42 percent and characterized by decreased caking or complete absence of it. D coal from the Kurakhovka deposit contains only about 2 percent sulfur.

Experimental coking of a charge containing 10 percent D coal in the Yenakiyevo Coke By-Products Plant in 1950 and 1952 indicated that blast furnaces of medium size (up to 800 cubic meters) can operate normally on the coke obtained. Best results are obtained from a charge with the following contents: 10 percent D coal, 17 percent G, 25 percent K, 48 percent PZh. Thus D coal replaces short-supply PS coal in the charge.

As in the case of G coal, charges containing D coal yield a lowered coke output but an increased output of chemical products. The possibility must be investigated of increasing a single load in a coke oven, the charge of which contains D coal by using microquantities of organic liquids. This will permit compensation for the noted lowering in the gross coke output.

The steady development of coal extraction in operating mines and the introduction of new seams and levels in place of worked out ones are changing considerably the character of the quality of coal being mined. In some cases, a mine begins to yield coal of a different type or technological group, or even fuel coal in place of coking coal, or vice versa.

Changes in the properties of coal during exploitation operations must be promptly revealed and taken into account to prevent losses of coal for coking. Coals must be investigated regularly, both for coking and fuel purposes. They must be periodically tested for plasticity, and the proportion of individual seams in the output must be determined. When coal suitable for coking is discovered among fuel coal particularly short-supply types or low-sulfur varieties, separate removal of these types must be arranged for so that valuable coals may not be lost in mixture with juel coal.

In case of a sharp deterioration in the quality of commercial coals, in coking properties or sulfur content, the reason for this deterioration should be established through plasticity tests.

Technological Grouping of Certain USSR Coals

GOST 1280-48 specifies standard technological grouping of coals of the Kuzbass, Karaganda, and the Kizel Basin, based on plasticity indexes and the volatilematter content.

With a volatile-matter content in the combustible mass of 24.5-25 percent and the thickness of the plastic layer 14 millimeters, the coals belong to group KZh, if the plasticity curve has a wavy or zigzag shape, and to KZh2, if the

With a volatile matter content in the combustible mass of 22-25 percent and the thickness of the plastic layer 13-14 millimeters, coals may belong to group K or KZh2 and, with the volatile matter content 24.5-25 percent and the thickness of the plastic layer more than 14 millimeters, to group K or KZh. In both cases, coals must be divided according to the amount of plastic shrinkage, which, for group KZh and KZh2, is more than 28 millimeters but for group K is not more than 28 millimeters.



STAT



Technological Grouping of Coals for Coking for Eastern Regions

	·	Per Volati	cent of le Matter	Plas	kness of tic Layer (mm)
Coals	Group Designation	From	То	From	То
Kuzbass					<u> </u>
Gas coal group I	Gl	More t	han 37	17	25
Gas coal group II	G2	More t	han 37	13	16
Fat coal group I	Zhl	Less t	han 33	More	than 25
Fat coal group II	Zh2	33	38		than 25
Coking fat coal	KZh	24.5	28	14	25
Coking fat group I	KZh1	28	31	14	25
Coking fat group II	KZh2	22	25	12	2) 14
Coking coal	К	19	25	13 or	
Coking coal group I	Kl	17	21	10	12
Coking coal group II	K2	17	21	7	
Lean caking	TS	Less th		6	9
Karaganda		•	,	Ü	9
Fat coal	Zh			20	
Coking coal group I	K1			20 or :	
Coking coal group II	K2			8	19
Kizel Basin	ı			Ü	11
Gas coal group I	Gl			11	12
Gas coal group II	G2			8	13
Fat coal group I	Zh1		-		10
Fat coal group II	Zh2			19 or m	ore 18

The Khar'kov Sc ntific Research Institute of Coal Chemistry (UKhIN) has worked out a techny sgical grouping for Donbass coals, indicated in the following table. In the case of coals without a clearly determined demarcation in their volatile-matter content, the following is recommended:

1. Coals with a volatile-matter content of 26 percent and a plastic layer 21 millimeters or more thick are to be assigned to group KZh if the plasticity curve has a zigzag shape and to Zhl if the curve is hump-shaped.

- 2. Coals with a volatile-matter content of 35 percent and a plastic layer more than 21 millimeters in thickness are assigned to group Gl if the plasticity curve is zigzag in shape and to Zhl and Zh2, depending on the thickness of the plastic layer when the curve is hump-shaped.
- 3. Coals are assigned to group PS2 only when there is obtained from them completely caked laboratory-crucible coke with absence of uncaked dust.

Technological Grouping of Coals for Coking for the Donbass

			-		-0110000	
Trad Bran		Conventional Designation of Group	Thickness tic Layer	of Plas (mm)		ercent of
ם	Long-flame, group l		From	To	From	To
D		D1	5	8	More	than 42
G	Long-flame, group II	D2		5*		than 42
_	Gas, group I	G1	16 or more			
G	Gas, group II	G2	9		35	44
PZh	Fat gas	ZhG	-	15	35	1,14
PZh	Fat, group I		12	20	26	35
PZh		Zh1	21	29	26	35
	Fat, group II	Zh2	30 or more		26	35
K	Coking fat	KZh	21 or more			
K	Coking	К			18	26
PS	Additive caking,	 .	15	20	18	26
	group I	PS1	8	14	10	_
PS	Additive caking,		•	14	12	26
	group II	PS2		7 *	12	18
T	Lean	T				
				4*	Less tha	n 17

*Less than or equal to figure

Lists of Certain USSR Mines Which Produce Constituents of Coking Charges

The following mines in the Donbass produce coal suitable to enter into a coking charge (according to data for 1952):

al

~



Trust		
	Mine	**
Kalininugol'	No. 3 C-313	Type of Coal
	No 3 Solidarnost	PZh
	No Sa imeni Stalin	
	No 9	K, PS K
	No 71	PZh
	Zapereval'naya	K
	imeni Kalinin	ĸ
	Novo-Kondrat'yevka	ĸ
	imeni Rumyantsev	PS, T
Dzerzhinskugol'	•	PZh
word801.	No 3 imeni Artem	
	NO O Derezovka	PZh
	Chegari	PZh
	imeni Dzerzhinski.	PZh
	imeni Voroshilov	PZh
	No 1/1 bis	PZh
Ordzhonikidzeugol'		G
	No 1/2 Krasnyy Oktyabr	
	THICHT DEF! MONE	PS, T
	Arasnyy Profintern	ĸ
	Yunkom	PS
Krasnoarmeyskugol'		·PS
	No 1 Novo-Grodovka	
	NO I Tsentrel trace	G
	NO I Kodinskara	G
	NO 1/2 Dobropolina	G
	NO 3	G
	No 5/6 imeni Dimitrov	G
	NO 12 bis	G
	No 17/18 imeni RKKA	G
	NO 30 Kurakhovalas	G
	No 40 Kurakhovskaya	D
Stalinugol'		D
U	No 1 imeni Chelyuskintsy	•
		G
	NO 4/21 imeni Molotani	G
	3.0 1/1/ Dis	PZh
	No 19	PZh
	No 29 imeni Stalin	PZh
	140 30	PZh
	No 31	PZh
	Petrovo-Lidiyevka	PZh, K
Kuybyshevugol'		, G
u -	No 1 Kamenka	
	1/2 Smolyanka	PZh
	No 1/7 Vetka	G
	No 4 imeni Gor'kiy	PZh
	NO 4 Livenka	G, PZh
	No 5/6 imeni Kalinin	PZh, K
	NO (/O lmeni Kelinin	K K
	No 10-bis	G.
	No 12 imeni F. Kon	-
	No 13 Nikopol'-Mariupol'skaya.	PZh G
		G
	imeni Gor'kiy Vladimir	G
	Viadimir Proletarka	G, PZh
	Teantral traces of	G PZn
	Tsentral'naya Zavodskaya imeni Kaganovich	K
	waganovich	G G

Trust	Mine	Type of deal
Budennovugol'	No 1/2 Livenka No 6 Krasnaya Zvezda No 6 Kapital'naya	Type of Coal PS PS
٠.	No 8 Chulkovka No 9 Naklonnava No 9 Kapital'naya No 11/21	PS PS PS PS
	No 12 Naklonnaya No 12/18 imeni Pravda No 16 Kucherovo	PS PS PS
	No 16/17 Yevdokiyevka Livenskaya Zapereval'naya Novo-Mushketovo	PS PS PS K
Makeyevugol'	Mushketovskaya Vertikal'naya	PS
o a ragoz	No 1 Sofiya No 1 Almaz No 9	PZh K
	No 10 Kholodnaya Balka No 14/18 Kholodnaya Balka	PZh K
	No 16 Kholodnaya Balka No 25 bis No 29	к к
	No 34	К
	No 46 imeni Lenin	PZh ~
	No 51	G
	Gruzskaya Naklonnaya	K PZh
	Proletarskava Krutava	r <i>zn</i> K
	imeni Kaganovich Kapital'naya Markovka	PZh, K
	imeni Lenin	PZh
Krasnogvardeyskugol:	Proletarskaya Glubokaya	PZh PZh
a analyzingOT	No 1 Shcheglovka No 1 Ganzovskaya	PZh
	No 3	PZh
	No 23	PZh
	No 6 No 6/13	PZh PZh
	No 6/14	G
	No 12/13 Grigor'yevka Mariya	PZh PZh
	imeni Ordzhonikize Chaykinoyuzhnoye	PZh PZh
	Novo-Butovke	PZh
Sovetskugol'	No 1 imeni Kirov	G
	No 1 Kholodnaya Balka	ĸ
	No 3/5 Butovka	PS
	No 3/5 Yasinovka	G PZh
	No 3 imeni Shmidt No 4/13 imeni Kirov	PS
	No 12-bis	PZh
	No 13-bis	PZh PZh v
	No 19/20 . Yasinovskaya	PZh, K K
	No 21 imeni Khrushchev	ĸ
	Ampital'nava Nolineuro	K, PS
	Kirovskaya Zapadnaya	K PZh

Trust	Mine	
Ymnana.		Type of Coal
Krasnodonugol'	No 1-bis	-SPC OI COMI
	No 1/2 V	ĸ
o	No 1/2 Krasnodarskaya	PS
	no a Severo-Gundonovales	
		PZh
	No 2-9 Krasnyy Oktyabr'	PZh
	70 J-018	PZh
	No 7 Izvarino	PS
	No 12	PZh
	No 17	PS
	No 18	PS
	No 20	K
	No 21 Sorokino	K
	No 22	ĸ
	No 173	PZh
	No 178	PZh
	Churd Line as	K
	Churilino Vostochnaya	PZh
	Churilino Zapadnaya	
••	Uralokavkazkaya	PZh
Kadiyevugol'	N ~ /-	G
_	No 3/3 bis	
	No 4/2 bis	PZh
	No 6 Maksimovka	PZh
	No 18	PZh
	No 36	PZh
	imeni Stalin	P2h
	imeni Il'ich	PZh
	No 1-bis Krivorozh'ye	PZh
	No 2/5 Kenka	ĸ
	No 4 Mazurovskaya	ĸ
	No 5 Stal	ĸ
	No 6/6-bis	PZh
	NO O/O-Dis	K
	No 11 Rau	
	No 12 imeni Dzerzhinskiy	K, PZh
	NO ZI-DIS	K
	No 50 Galki	PS
	Karmatorskaya	K
	Davydovskaya	PZh
Voroshilovugol'		PZh
. orosuriovugor.	No 2 Del'ta	
	No 5-bis	T
	No 6-bis Belyanka	T
	No 10 imeni Artem	PS
	No 25	PS
	No 19	PS
	70000001	Ğ
•	Zapereval'naya	ř
	imeni Stalin	
	Tsentral'naya Belyanka	PS
	imeni lenin	K
	imeni Voroshilov	G
Pervomayskugol'		ĸ
	.7o 1	
	No 4/5 Sokologorovka	PZh
	10 4/0 Karbonit	G
	Pervomayskaya	G .
	No 1 Bezhanovka	G
	No 2 Bezhanovka	G
	No 1/2 Novo-Golubovskaya	Ğ
	/c novo-Golubovskaya	



Trust Mine Type of Coal Pervomsyskugol' No 4 Golubovskaya G No 5 No 6 imeni Kirov G G G No 22 imeni Kirov No 77 No 100-bis Ğ No 102 Velikan G Gurdorovugol' No 1 Severo-Izvarinskaya K PZh PS K K K K No 3 Severo-Gundorovskaya No 12-bis No 15-bis No 20 No 21 No 22 No 54 Yugo-Vostochnaya Yugo-Zapadnaya K K Bogurayevugol' No 5 Pastukhovskaya PS No 6 Vail'yevskaya PS No 13 Gornyatskaya ĸ No 23 Pastukhovskaya PS Gornyatskaya Vostochnaya

The following Kuzbass mines produce coal suitable for use in coking charges (according to data for 1951 and 1952):

Trust	Mine	Type of Coal
Stalinugol	imeni Stalin imeni Molotov No 3/3-bis Vostochnaya Magar k	K, K2, SS K, K2 K, K2 K K
Prokop'yevskugol'	imeni Voroshilov imeni Kalinin imeni Kaganovich Ziminka Krasnogorskaya Maneikha	K, K2 K K, K2, SS K, K2 K K2, SS
Kaganovichugol'	imeni Vakhrushev No 1/2 No 4 Surtaikha No 7a No 76	K, K2 K, K2 K2 K2 K K
Molotovugol'	Kapital'naya I Kapital'naya II No 4 No 9	PZh PZh PZh PZh



STAT

Trust	Mine	M
Variable		Type of Coal
Kuybyshevugol	Baydayevskaya Abashevskaya No 1 Abashevskaya No 2 Zyryanovskaya	PZh PZh PZh G
Leninugol'	imeni Ye. Yaroslavskiy	
	imeni Kirov	G
	Polsayevskaya I	G
	7 Noyabrya	G
	Moyabrya	G
Belovugol'	Rehamely	
_	Babanakovskaya	PZh
	Pionerka	G
	Babanakovskaya II	PZh
Anzherovugol'	No 5/7	
	No 9/15	PS
	Fizkul'turnik	PS
	T.TEVOT. COLUIK	PS

Listing of Certain Donbass Coal-Cleaning Plants

An OF is a coal-cleaning plant serving one mine at which it is located. A TsOF is a central coal-cleaning plant and serves a group of mines. The following OFs and TsOFs are under the jurisdiction of the Stalinugleobogashcheniye Trust: OF Novo-Kondrat'yevka, OF No 4/5 Nikotovka, OF Komsomolets, TsOF Novo-Uzlovskaya, TsOF Kal'miusskaya, TsOF imeni Dzerzhinskiy, OF No 13-bis, OF No 1 Tsentral'naya, and OF No 1/2 Dobropol'ye.

The following OFs and TsOFs are under the jurisdiction of the Voroshilov-gradugleobogashcheniye Trust: OF No 1-bis Krivorozh'ye, TsOF Irminskaya, TsOF Bryanskaya, OF imeni Stalin, and TsOF Novo-Golubovskaya.

The TsOF Chumakovskaya is subordinate to Glavkoks.

- E N D -

